

# CP-UAR-0804P1-A

## 8Ch. Full 960H DVR



Krypto Series

### Main Features

- ⇒ Up to 8 cameras with 960H Realtime Preview
- ⇒ H.264 dual-stream video compression
- ⇒ All channel 960H Realtime Recording
- ⇒ HDMI / VGA / TV simultaneous video output
- ⇒ Support 1 SATA HDD up to 4TB, 2 USB2.0
- ⇒ Mobile Software: CMOB
- ⇒ CMS Software: KVMS



Feature	Specification
Processor	High performance embedded microprocessor
Operating System	Embedded LINUX
System Resources	Pentaplex function: live, recording, playback, backup & remote access
User Interface	GUI
Control Devices	Front panel, USB mouse, IR remote control, Keyboard, Network
Video Input	8 channel, BNC
Video Output	1 HDMI, 1 VGA, 1 TV, BNC(1.0Vp-p, 75Ω)
Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Compression	H.264 / G.711
Video Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600
Video Recording	960H(1~25/30fps),
Extra Stream	CIF/QCIF(1~25/30ps)
Video Display Split	1/4/8/9
Privacy Masking	4 rectangular zones (each camera)
Audio Input	4 channel, RCA
Bi-directional Talk Input	Reuse audio input/output channel 1
Audio Output	1 channel, RCA
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Alarm Input	8 channel
Alarm Output	3 channel
Hard Disk	1 SATA port, up to 4TB
Smart Phone	iPhone, iPad, Android, Windows Phone

Feature	Specification
Trigger Events	Recording, Tour, Video Push, Email, FTP, Buzzer & Screen tips
Recording Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Max User Account	20 users
Interface Ports	2 USB 2.0, 1 RS485, 1 RJ45
Ethernet	RJ-45 port (10/100M)
Protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Temp	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimensions	325mm×245mm×45mm
Weight	1.5KG(without HDD)



1141 Budapest, Fogarasi út 77.      1095 Budapest, Mester u. 34.  
 Tel.: \*220-7940, 220-7814, 220-7959,      Tel.: \*218-5542, 215-9771, 215-7550,  
 220-8881, 364-3428 Fax: 220-7940      216-7017, 216-7018 Fax: 218-5542  
 Mobil: 30 531-5454, 30 939-9989      Mobil: 30 940-1970, 20 949-2688

**www.cpplus.hu**

E-mail: [info@delton.hu](mailto:info@delton.hu) Web: [www.delton.hu](http://www.delton.hu)